



Sonic 2024
with optional mount

The world's first broadband-wideband high resolution multibeam sonar for unprecedented system versatility, productivity and performance. Offers low power consumption and depth rating up to 6000m, making this model ideal for integration to ROV or AUV, for use in a wide range of applications including construction and monitoring, pipeline inspections and cable route surveys.

Additional features & benefits of the technologically advanced, user-friendly **Sonic 2024 Series:**

- ▶ Technical modes that can be upgraded remotely, anytime:
 - Ultra-high Resolution (UHR)
 - Pipeline mode
 - TruePix™ Compressed water column
 - Multispectral backscatter
 - Forward looking sonar (FLS)*
- ▶ Ultra-High Density (UHD), 1024 soundings per ping, resulting in greater resolution, particularly on the outer beams
- ▶ Selectable operating frequencies 'on-the-fly' in steps of 1Hz so you can choose the best frequency for the application or environment
- ▶ Dynamic focusing, essential to ensure high resolution in very shallow waters
- ▶ ROBO™ mode for simpler operation
- ▶ Runs on the Sonic Control Graphic User Interface
- ▶ The Integrated Sonic Series exceeds IHO-S44 Special Order when installed following R2Sonic manual instructions
- ▶ Value priced



Highly Portable



SV probe

Introducing the new **Sonic 2024-V Series**, with embedded IMU – first on the market!

The V-Series is an innovative, integrated solution. An enhanced version of the standard 2024 product that offers additional unique user benefits:

- ▶ New embedded Inertial Measurement Unit (IMU)
 - Single cable, less space and less risk of exposure than with a separate IMU
 - Improved performance with roll/pitch accuracy to 0.015°
 - Highly immune to GNSS outages
- ▶ New compact VOX-IM
 - Integrated connectors for additional motion/GPS equipment
 - RTK/RTCM input
 - Wide range of voltage input – AC and DC
- ▶ New VOX-App user interface
 - Easier system set up and interfacing with new embedded IMU / GNSS
 - Enhanced visual package and user interface



SIM Box



New Compact VOX-IM

Easy to Integrate on any platform



AUV*



ROV*



ASV/USV



Small Vessel

Extra Light & Compact!



New VOX-App User Interface

	Sonic 2024	Sonic 2024-V
Selectable Frequencies		170kHz – 450kHz (optional 700kHz)
Minimum frequency increase		1Hz
Beamwidth, across track and along track		0.3° x 0.6° at 700kHz (optional) 0.45° x 0.9° at 450kHz 1° x 2° at 200kHz
Number of soundings		Up to 1024 soundings per ping
Max speed (vessel)		11.1 knots for full coverage (The speed of the survey is primarily limited by the installation of the multibeam echosounder)
Near-field focusing		Yes
Roll stabilized beams		Yes
Pitch stabilized beams		No
ROBO™ Automated Operation		Auto power, gain and pulse width
RangeTrac™, GateTrac™		Yes
Saturation Monitor		Yes
Selectable Swath Sector (Max Coverage)		10° to 160° Or up to 160° through engineering command User selectable in real-time
Sounding Patterns		Equiangular Equidistant single / double / quad modes Ultra High Density (UHD)
Sounding Depth		up to 400m+
Pulse Length		15µs - 1ms
Pulse Type		Shaped CW
Ping Rate		up to 60Hz
Bandwidth		up to 60kHz
Immersion Depth	100m Optional 4000m & 6000m FLS projectors are rated 3000m	100m
Bottom Detect Resolution		3mm

Mechanical Specifications

	Sonic 2024	Sonic 2024-V
Receiver Dim (LWD)		480 x 109 x 190mm
Receiver Mass		12.9kg
Projector Dim (LWD)		273 x 108 x 86mm
Projector Mass		3.3kg
Sonar Interface Module (LWD)	280 x 170 x 160	212 x 160 x 70.5mm
Sonar Interface Module Mass	2.4kg	2.9kg

Graphical User Interface (GUI)

	Sonic Control 2024	VOX-App
Mains	90-260V AC, 45-65Hz	90-260V AC or 10-55V DC
Power Consumption		50W avg
Uplink / Downlink		10/100/1000Base-T Ethernet
Sync in, Sync out		TTL
Deck cable length		15m, optional 25m and 50m

Sonic 2024-V INS Accuracies (with RTK)

Roll & Pitch	0.015°
Heading	0.015° with baseline >4m, 0.03° with baseline >2m
Heave	5cm or 5% real-time, 2cm or 2% delayed-heave
Position	Horizontal: 1cm + 0.5 ppm, Vertical: 1.5cm + 1 ppm

R2Sonic Service & Support

- ▶ Technical support 24/7/365, globally
- ▶ Firmware of all MBES can be upgraded remotely at no charge
- ▶ Fast, quality repairs performed by our team that engineered the multibeam sonar and the IMU
- ▶ 3-year standard warranty, upgradable to 6-years to further minimize your risk on investment
- ▶ Theoretical and hands-on personalized training delivered by our experts

Please contact us or visit r2sonic.com/products for more info.



US Patents: 10,132,924 • 10,605,914 • 11,079,490 EU Patent: EP3362817

